

Maytag® Jetclean® II Dishwashers

Maytag® Portable Dishwasher

Models	With FlexLoad™ Third Rack										MDCS100
	MDB9750	MDB9600	MDB8600	MDB8750	MDB7750	MDB7650	MDB7600	MDB6600	MDB5600	MDB4650	
ENERGY STAR®-Qualified	★	★	★	★	★	★	★	★	★	★	
Stainless Steel Interior	■	■	■	■	■	■	■	■	■	■	
<b>CONTROL FEATURES</b>											
Microprocessor Controls With Touch Pads	13	13	11	11	6	11	11	11	10	6	9
Semi-Integrated Control Panel	■	■	■	■	■	■	■	■	■	■	
Water-Heating Control	ATC*	ATC*	ATC*	ATC*	ATC*	ATC*	ATC*	ATC*	ATC*	ATC*	AccuTemp™
Precision Clean™ Turbidity Sensor	■	■	■	■	■	■	■	■	■	■	
<b>CYCLES</b>											
Heavy Wash Cycle	■	■	■	■	■	■	■	■	■	■	
Normal Wash Cycle	■	■	■	■	■	■	■	■	■	■	
Light Wash Cycle	■	■	■	■	■	■	■	■	■	■	
Rinse Only Cycle	■	■	■	■	■	■	■	■	■	■	
Auto Clean Cycle	■	■	■	■	■	■	■	■	■	■	
Quick Wash Cycle	■	■	■	■	■	■	■	■	■	■	
<b>OPTIONS</b>											
Sanitize Option	■	■	■	■	■	■	■	■	■	■	
ToughScrub™ Option	Plus	Plus	■	■	■	■	■	■	■	■	
Extra Rinse Option	■	■	■	■	■	■	■	■	■	■	
Delay Wash Option	1-To 9-Hour	1-To 9-Hour	1-To 9-Hour	1-To 9-Hour	2-/4-/6-Hour	1-To 9-Hour	1-To 9-Hour	2-/4-/6-Hour	2-/4-/6-Hour	2-/4-/6-Hour	2-/4-/6-Hour
Control Lockout	■	■	■	■	■	■	■	■	■	■	
160-Degree Wash	■	■	■	■	■	■	■	■	■	■	
Time Remaining Display	■	■	■	■	■	■	■	■	■	■	
Indicator Lights	15	15	16	16	13	13	16	17	16	13	15
<b>HEATED DRY SYSTEM</b>											
Active-Vent Dry System	■	■	■	■	■	■	■	■	■	■	
Ventless Drying	■	■	■	■	■	■	■	■	■	■	
<b>ALL-RACK OPTIONS</b>											
Rack Finish	Nylon	Nylon	Nylon	Nylon	Nylon	Nylon	Nylon	Nylon	Vinyl	Vinyl	Vinyl
Ball-Tip Tines	■	■	■	■	■	■	■	■	■	■	■
Stainless Steel RollerGlide™ Tracks	■	■	■	■	■	■	■	■	■	■	■
Stainless Steel Tracks	■	■	■	■	■	■	■	■	■	■	■
<b>UPPER-RACK OPTIONS</b>											
Vari-Lock™ Snigger	■	■	■	■	■	■	■	■	■	■	■
Adjustable Upper Rack	■	■	■	■	■	■	■	■	■	■	■
Removable Upper Rack	■	■	■	■	■	■	■	■	■	■	■
Tiered Upper Rack With Shelf	■	■	■	■	■	■	■	■	■	■	■
Fold-Away™ Tines	■	■	■	■	■	■	■	■	■	■	■
Cup Clips	■	■	■	■	■	■	■	■	■	■	■
<b>MIDDLE-/LOWER-RACK OPTIONS</b>											
Adjustable Middle Rack	■	■	■	■	■	■	■	■	■	■	■
Removable Middle Rack	■	■	■	■	■	■	■	■	■	■	■
Fold-Away™ Tines Middle Rack	■	■	■	■	■	■	■	■	■	■	■
Convertible Bowl Tines	■	■	■	■	■	■	■	■	■	■	■
Tiered Middle Rack	■	■	■	■	■	■	■	■	■	■	■
High-Side Rack With Shelf	■	■	■	■	■	■	■	■	■	■	■
FlexLoad™ Third Rack	■	■	■	■	■	■	■	■	■	■	■
<b>WASH SYSTEM</b>											
Rinse-Aid Dispenser	■	■	■	■	■	■	■	■	■	■	■
Wash Levels/Tiers	7/10	7/10	7/10	5/7	5/7	5/7	5/7	5/7	5/7	5/7	3/6
Multifiltration	■	■	■	■	■	■	■	■	■	■	■
Stainless Steel Hard Food Disposer	■	■	■	■	■	■	■	■	■	■	■
<b>SILVERWARE BASKET</b>											
Split & Fit™ Silverware Basket	Deluxe	Deluxe	Deluxe	■	■	■	■	■	■	■	■
One-Piece Removable Basket With Handle	■	■	■	■	■	■	■	■	■	■	■
Odds & Ends Basket	■	■	■	■	■	■	■	■	■	■	■
Utility Basket	■	■	■	■	■	■	■	■	■	■	■
<b>SOUND OPTIONS</b>											
Sound Package	QuietSeries™ 300 SS	QuietSeries™ 300	QuietSeries™ 300	QuietSeries™ 200 SS	QuietSeries™ 100 SS	QuietSeries™ 300	QuietSeries™ 300	QuietSeries™ 200	QuietSeries™ 100	QuietSeries™	Quiet Pack
<b>COLOR AVAILABILITY</b>											
White	■	■	■	■	■	■	■	■	■	■	■
Bisque	■	■	■	■	■	■	■	■	■	■	■
Black	■	■	■	■	■	■	■	■	■	■	■
Stainless Steel	■	■	■	■	■	■	■	■	■	■	■
Optional Wood Panel Kit	DAX3090	DAX3090	DAX3000	DAX3000	DAX3000	DAX3090	DAX3000	DAX3000	DAX3000	DAX3000	DAX1000
Optional Monochromatic Side Mounting Strips	DAX3200	DAX3200	DAX3200	DAX3200	DAX3200	DAX3200	DAX3200	DAX3200	DAX3200	DAX3200	
Optional Toe Panel Extension Kit	DAX3400	DAX3400	DAX3400	DAX3400	DAX3400	DAX3400	DAX3400	DAX3400	DAX3400	DAX3400	

\* Automatic Temperature Control

**Maytag® Jetclean® II Dishwashers**

Dishwasher Dimensions	
■	in. (cm)
A	23 3/8 (60.6)
B	19 1/2 (49.5)
C1	33 3/4 (85.1) min. 35 1/4 (89.5) max.
C2	33 3/4 (85.7) min. 35 1/4 (89.5) max.
D	23 3/8 (60.6)

**Note:** When installing the dishwasher in or near a corner, allow enough room for the door to open without interfering with any cabinet drawers or hardware.

**WOOD DECORATOR PANELS**  
Wood decorator panel kits are available. Please contact dealer for more information.

**Maytag® Dishwashers**

Dishwasher Dimensions	
■	in. (cm)
J	23 3/8 (60.6)
K	21 (53.3)
L	33 3/4 (85.7) min. 35 1/4 (89.5) max.
M	25 (63.5)


**Portable Dimensions — in. (cm):**  
Width: 24 1/4 (61.6)  
Depth: 28 (71.1)  
Height: 36 1/2 (92.7)

**Note:** When installing the dishwasher in or near a corner, allow enough room for the door to open without interfering with any cabinet drawers or hardware.

Models	MDB4601	MDB3700
ENERGY STAR®-Qualified	★	
<b>CONTROL FEATURES</b>		
Microprocessor Controls With Touch Pads	8 Pads	
Timer Controls With Push Buttons		6 Push Buttons
Water-Heating Control	AccuTemp™	Temp Boost™
<b>CYCLES</b>		
Heavy Wash Cycle	■	■
Normal Wash Cycle	■	■
Light Wash Cycle	■	■
Pots & Pans	■	■
Rinse Only Cycle	■	■
<b>OPTIONS</b>		
High-Temperature Wash	■	■
Delay/Resume Option	2-/4-/6-Hour	2-/4-/6-Hour
Passive-Vent Dry System	■	■
Rinse-Aid Dispenser	■	■
<b>ALL-RACK OPTIONS</b>		
Rack Finish	Vinyl	Vinyl
Ball-Tip Tines	■	■
Deluxe Upper Rack	With Shelf	With Shelf
One-Piece Silverware Basket	Removable	Removable
<b>SOUND OPTIONS</b>		
Sound Package	QuietSeries™ 100	QuietSeries™ 100
<b>COLOR AVAILABILITY</b>		
White	■	■
Bisque	■	■*
Black	■	■*
Optional Wood Panel Kit	DAX1000	DAX1000

Model MDB4601 will be available in March 2005.  
\*Color only available until March 2005.

Exterior Color Options



**DAX1000 DECORATOR PANEL INSTALLATION\* (WOOD)**

Models		Access Panel Dimensions	
MDCS100, MDB4601, MDB3700		in. (cm)	
■	in. (cm)	■	in. (cm)
A	23 3/8 (59.8)	A	23 1/8 (60.2)
B	18 3/8 (46.2)	B	4 3/8 (11.7)
C	1 (2.5) min.	C	7/8 (0.5)
D	3/8 (1) max. thickness	D	7/8 (0.5)
E	1/4 (0.6)	E	1/4 (0.6)
F	1/8 (0.3)		
G	1/4 (0.6)		
H	1/8 (0.3)		

**Note:** 1. 1/8" maximum thickness in this area.

\*Requires kit DAX1000AXX (kit includes auxiliary door springs to compensate for added weight of wood panel; maximum door panel weight is 11 1/2 lbs.). Wood panels should be coated with a protective finish (varnish or polyurethane).

Dishwasher Cabinet Opening

- Locate preferred drain area.
- Keep back free of drain, water and electrical supply.
- Minimum 32" drain hose height, minimum 1/2" drain line. Floor drains require a siphon break.
- Electrical and plumbing should meet all local and national codes.
- Electrical and water supplies should enter cabinet opening on the floor or through the back or side walls, as shown in the shaded portion of drawing.
- Connections preferably located toward left side of dishwasher. Care should be taken to route water and electrical away from motor and blower (if equipped).
- When dishwasher is installed in or near a corner, allow enough room for the door to open without interfering with cabinet drawers or hardware.

Maytag® Food Waste Disposers

Models	Continuous-Feed						Batch-Feed
	DFC7500	DFC5500	DFC1500	L40-C	L20-C	L20	DFB6500
<b>FEATURES</b>							
Split-Phase Induction Motor	■	■	■	■	■	■	■
Horsepower	1	3/4	1/2	1/2	1/3	1/3	3/4
Overload Protection With Manual Reset	■	■	■	■	■	■	■
Automatic Reverse	■	■	■	■	■	■	■
Capacity — oz.	50	26	26	26	26	26	64
Stainless Steel Grinding Chamber	■	■	■	■	■	■	■
ABS Grinding Chamber	■	■	■	■	■	■	■
Stainless Steel Swivel Impeller	■	■	■	■	■	■	■
Stainless Steel Grinding Elements	■	■	■	■	■	■	■
Galvanized-Steel Grinding Elements	■	■	■	■	■	■	■
QuickConnect Mounting	■	■	■	■	■	■	■
Stainless Steel Sink Flange	Polished	Polished	Polished	■	■	■	Polished
Sound Insulation	QuietGrind™ 200	QuietGrind™ 100	QuietGrind™	■	■	■	QuietGrind™ 300
Polypropylene Stopper	■	■	■	■	■	■	■
Stainless Steel Stopper	One-Piece	■	■	■	■	■	Two-Piece
Self-Service Wrench	■	■	■	■	■	■	■
Cushioned Anti-Splash Baffle	Deluxe	Standard	Standard	Standard	Standard	Standard	Deluxe
Dishwasher Drain Connection	Bolted	Threaded	Threaded	Threaded	Threaded	Threaded	Bolted
Color Availability	Black	Black	Black	Black	Black	Black	Black
Warranty	5-Year	4-Year	3-Year	1-Year	1-Year	1-Year	5-Year
Weight — lbs. (kg)	20 1/2 (9.3)	16 1/2 (7.5)	14 1/2 (6.6)	14 1/2 (6.6)	13 1/2 (6.1)	13 1/2 (6.1)	24 (10.9)

All models listed may not be available from every Maytag dealer. Because of continuing product improvement, Maytag reserves the right to change specifications without notice.

DAX3090/DAX3000 PANEL INSTALLATION\*\* (WOOD)

DAX3090 — MODELS MDB7650, MDB9600, MDB9750		DAX3000 — MODELS MDB4650, MDB5600, MDB6600, MDB7600, MDB8750, MDB8600, MDB8750	
■	in. (cm)	■	in. (cm)
A	25 1/8 (65.9)	A	25 (63.5)
B	23 3/8 (59.2)	B	23 3/8 (59.2)
<b>Spacer Panels</b>			
■	in. (cm)	■	in. (cm)
C	1 1/4 (3.2)	C	23 1/8 (60.2)
D	23 1/8 (60.2)	D	24 3/8 (62.9)
E	3 (7.6)	E	3 (7.6)
F	3 (7.6)	F	3 (7.6)

**Note:** Door panels may be 1/4" (6.4 cm) or 1/2" (1.9 cm) thick. 1/4"-thick door panels require the addition of 1/4"-thick spacer panels as indicated by the shaded areas in the diagram. 1/4"-thick door panels should be installed without spacer panels. See installation guide included with kit for complete specifications.

\*\*Requires kit DAX3000AXX or DAX3090AXX (kit includes auxiliary door springs to compensate for added weight of wood panel and all applicable shims; maximum total panel weight is 13 lbs.). Wood panels should be coated with a protective finish (varnish or polyurethane).

IMPORTANT